

Navicross® 0.018"

Support Catheters

R2P Navicross®

Support Catheters

R2P NAVICROSS® Support Catheters

PRODUCT CODE	WIRE COMPATIBILITY (in)	CATHETER LENGTH (cm)	TIP SHAPE
SC-R35STR200	0.035"	200 cm	Straight
SC-R35ANG200	0.035"	200 cm	Angled

NAVICROSS® Support Catheters

PRODUCT CODE	WIRE COMPATIBILITY (in)	CATHETER LENGTH (cm)	TIP SHAPE
NC35650	0.035"	65 cm	Straight
NC35651	0.035"	65 cm	30° Angle
NC35900	0.035"	90 cm	Straight
NC35901	0.035"	90 cm	30° Angle
NC35130	0.035"	135 cm	Straight
NC35131	0.035"	135 cm	30° Angle
NC35150	0.035"	150 cm	Straight
NC35151	0.035"	150 cm	30° Angle

NAVICROSS® 0.018" Support Catheters

PRODUCT CODE	WIRE COMPATIBILITY (in)	CATHETER LENGTH (cm)	TIP SHAPE
NC18650	0.018"	65 cm	Straight
NC18651	0.018"	65 cm	Angle
NC18900	0.018"	90 cm	Straight
NC18901	0.018"	90 cm	Angle
NC18130	0.018"	135 cm	Straight
NC18131	0.018"	135 cm	Angle
NC18150	0.018"	150 cm	Straight
NC18151	0.018"	150 cm	Angle

NAVICROSS® Support Catheters - Product Specifications

	R2P NAVICROSS 0.035"	NAVICROSS 0.035"	NAVICROSS 0.018"
Effective Lengths	200 cm	65, 90, 135, 150 cm	65, 90, 135, 150 cm
Number of Radiopaque Markers	3	3	3
Distance from distal tip to first marker	2 mm	1 mm	1 mm
Radiopaque Marker Spacing	40 mm, 60 mm	40 mm, 60 mm	40 mm, 60 mm
Radiopaque Marker Sizing	0.7 mm, 1 mm, 1 mm	0.7 mm, 1 mm, 1 mm	5 mm, 10 mm, 10 mm
Maximum Guidewire Compatibility	0.035"	0.035"	0.018"
Maximum Injection Pressure	600 psi	750 psi	300 psi
Catheter Outer Diameter (OD)	4.5 Fr	4 Fr	2.6 Fr
Tip Design/Shape	Straight, Angled	Straight, 30° Angled	Straight, 30° Angled
Hydrophilic Coating	Distal 40 cm	Distal 40 cm	Distal 40 cm

FIND OUT MORE  Phone: 800.888.3786  terumo.com

RX ONLY. Refer to the product labels and package insert for complete warnings, precautions, potential complications, and instructions for use.

©2023 Terumo Medical Corporation. All rights reserved. All brand names are trademarks or registered trademarks of Terumo. PM-06729